Catalunya in GPM GV








X. Llort, D. Sempere-Torres, D. Velasco J.J. Pastor, E. Velasco S. Paricio

Membre de

XARXA DE GENTRES
DE SUPORT
A LA INNOVACIÓ
TEGNOLÓGICA

Amb l'acreditació de:







Grup de Recerca Aplicada en Hidrometeorologia
UNIVERSITAT POLITÈCNICA DE CATALUNYA

Where is Catalunya?



Catalunya and its characteristics



Catalunya is a good representative of Mediterranean regions

- Climate characterized by events of heavy rain with high spatial and temporal variability
- Driven by the interaction between marked orography and a warm sea
- Mean yearly precipitation between 300 and 700 mm
- Daily maximal precipitation: 1200 mm/day
- 10-year return period daily precipitation > 100 mm
- Daily precipitation > 200 mm




3 days/year somewhere

Catalunya and its characteristics

- One of the major urban areas on the Mediterranean: Barcelona (over 3 millions inhabitants)
- One of the most touristic areas of the world
- High sensitivity to floods (only on the Llobregat river basin 46 damaging floods from 1780)
- Wide social interest for precipitation measurements and forecasting

Catalunya and its characteristics



Urbanisation has occupied the flood prone areas

Advertisement:

Locate your house wherever you want...
But the loan do it at our Bank



Catalan National Network

Operational instrumentation at Catalunya


SAIH telemetered network


- o stage level
- oraingauges 🔾

METEOCAT network

raingauges

C-band, Doppler Radar network






Catalan National Network: RADARS

Vallirana (1997)

Puig d'Arques (2002)








Creu del Vent (2004)

Catalan National Network: RADARS



Catalan National Network: RAINGAUGES



Research Topics at GRAHI-UPC

- Hydrometeorological data correction chain and product generation: QPE.
- Precipitation forecasting: **QPF**.
- Rainfall-Runoff models and hydrological forecasting.
- Visualization and analysis tools for hydrometeorological data.
- Study of the error structure in radar estimates. Ensemble techniques.


Based on: Compare radar estimates against a Benchmark

Sempere-Torres, AMS2007; HAWR2008

Benchmark: The BEST 2D precipitation field estimate we are

able to obtain

- Using all the existing information (sometimes not available in real time)
- Allowing post-processing
- Allowing expert analysis



Based on: Compare radar estimates against a Benchmark

Sempere-Torres, AMS2007; HAWR2008


Benchmark: The BEST 2D precipitation field estimate we are

able to obtain

- Using all the existing information (sometimes not available in real time)
- Allowing post-processing
- Allowing expert analysis

Error definition:

$$Error = 10 \cdot Log_{10}(\frac{Benchmark}{RadarData})$$



Based on: Compare radar estimates against a Benchmark

Sempere-Torres, AMS2007; HAWR2008

Benchmark: The BEST 2D precipitation field estimate we are


able to obtain

- Using all the existing information (sometimes not available in real time)
- Allowing post-processing
- Allowing expert analysis

Error definition:


$$Error = 10 \cdot Log_{10}(\frac{Benchmark}{RadarData})$$

Generation of radar ensembles using the obtained error characteristics



Hydrological validation: Besòs TestBed


Besòs basin (1015 km²)



- Elevations: 0-1400m asl
- High urbanization degree
- Under the umbrella of 4 radars at distances below 100 km

Hydrological validation: Besòs TestBed

Besòs basin (1015 km²)



- Elevations: 0-1400m asl
- High urbanization degree
- Under the umbrella of 4 radars at distances below 100 km

 Real-time validation using Dichitop Rainfallrunoff Model

Hydrological validation: Besòs TestBed

The rainfall-runoff model Dichitop (Corral, 2004)

- Grid-based model able to use distributed rainfall fields.
- A lumped model is applied at hydrological cell scale.
- TOPMODEL in rural cells and SCS in urban cells.
- A simplified drainage network is used to transfer cell hydrographs.
- Basin hydrograph is calculated as the linear combination of cell hydrographs.



Range


SIGMA: Integrated Visualization tool

Catalunya

Spain)

- Radar Products
- MeteoSat Products
- Georef. Information
- NWP Models
- Lighting








Range

Catalunya

EHIMI (2002-2006)

Integrated System for HydroMeteorological Forecasting in Catalunya







Range

Catalunya

EHIMI (2002-2006)

Integrated System for HydroMeteorological Forecasting in Catalunya

- The main purpose of the EHIMI project was to implement a real-time hydrometeorological forecasting system based on weather radar information.
- EHIMI is composed by several modules and tools oriented, on one hand, to process and analyze 3-D radar data, and in the other hand, to process the conventional hydrological data (raingauges and stage sensors), obtaining an improved rainfall field based on a radarraingauge blending.
- EHIMI uses also a rainfall forecast, followed by the application of a distributed rainfall-runoff model (Dichitop), providing helpful information in order to manage floods in risky situations.



Radar Data










Hydrological Data




EHIMI (2002-2006)


Data Correction



Product Generation




Dissemination & Visualization



Range

EHIMI (2002-2006)





Range

EHIMI (2002-2006)

Catalunya

- Stability
- Screening effects
- Ground clutter suppression and substitution
- Attenuation
- Extrapolation to ground (VPR)






GenRad

Range

EHIMI (2002-2006)

Catalunya

MoViRad




Range

EHIMI (2002-2006)

Catalunya

MoViRad




Range

EHIMI (2002-2006)

Catalunya

Spain)

AniPRad



Range

Catalunya

EHIMI (2002-2006)

Integrated System for HydroMeteorological Forecasting in Catalunya



EHIMI - Phase II (2007-2010)



- Improvement of the Integrated Hydrometeorological System (radar data correction, raingauge merging, radar based nowcasting, rainfall uncertainties estimation)
- Extension of the FF early warning system to all catalan territory, based on high resolution hydrologic forecasting


Range TELVENT - EGMASA - INM (2007-2008)

(Catalunya)

- Implementation of an Integrated Hydrometeorological System (radar correction, raingauge merging) in Andalucia
- Radar data provided by INM radar network
- Implementation of the FF early warning system to 2 watersheds in Andalucia, based on high resolution hydrologic forecasting

Spain

Visualization integrated in G-Earth





Range

(Catalunya)

FLOODsite (2004-2009)

Integrated Flood Risk Analysis and Management Methodologies





- 'Global Change and Ecosystems' Program (6th EU Framework Program, FP6)
- The FLOODsite Project Team comprises some 37 partner organisations drawn from 13 different countries
- FLOODsite aims to deliver tools and methodologies to support integrated flood risk analysis and management.
- Seven Pilot Study Sites have been established within FLOODsite (being subject to flash floods). The purpose of the Pilot Sites is to provide real locations with real problems that participate as an integrated part of the research and development work.



EU

Range

HYDRATE (2006-2009)

(Catalunya)

Hydrometeorological data resources and technologies for effective flash flood forecasting




- STREP Project of the 6th EU Framework Program (FP6)
- The HYDRATE Project Team comprises 9 universities and 7 government research centres. These represent 8 Member States, 1 Associated Candidate State and 3 third-countries (12 Countries)
- The HYDRATE objective is to improve the scientific basis of flash flood forecasting, advancing a European-wide innovative flash flood observation strategy and developing a coherent set of technologies for effective early warning systems
- HYDRATE will develop a <u>freely-accessible European Flash Flood</u>
 <u>Database</u> to make available the collected hydrometeorological data to the international research community.







HYDRATE (2006-2009)




Range

(Catalunya)

EWASE (2006-2008)

Effectiveness and Efficiency of Early Warning Systems for Flash Floods



- project the 6th EU Framework Program (FP6)

 The Project Team comprises 2 universities and 2 engineering
- The Project Team comprises 3 universities and 2 engineering companies.
- Main objective of EWASE is to develop a methodology for the evaluation of Early Warning Systems' effectiveness and efficiency.
- For the evaluation two basic factors will be compared: the reliability of the provided forecasts as a function of lead time and the economic benefit of this information.
- An inter-comparison between 3 hydrologic models in 2 different test basins (Catalunya and Austria) will assess the uncertainties (using ensamble techniques) in the provided flow forecast.



EU

Catalunya in GPM GV

Thank you for your attention!




X. Llort, D. Sempere-Torres, D. Velasco J.J. Pastor, E. Velasco S. Paricio



Agència Catalana de l'Aigua

Membre de:









Grup de Recerca Aplicada en Hidrometeorologia UNIVERSITAT POLITÈCNICA DE CATALUNYA